

4DLCD-43480272-IPS Series

4DLCD-43480272-IPS
4DLCD-43480272-IPS-RTP
4DLCD-43480272-IPS-CTP
4DLCD-43480272-IPS-CTP-CLB

Datasheet

Revision 1.4

Copyright © 2024 4D Systems

Content may change at any time. Please refer to the resource centre for latest documentation.

Contents

1. General Specification	4
2. TFT LCD Display Drawing (Non-Touch Version)	0
3. TFT LCD Display Drawing (Resistive Touch Version)	0
4. TFT LCD Display Drawing (Capacitive Touch Version)	0
5. TFT LCD Display Drawing (Capacitive Touch Version with Cover Lens Bezel)	0
6. Absolute Maximum Ratings	0
7. Electrical Characteristics	0
8. Electro-Optical Characteristics	0
9. Backlight Characteristics	0
10. Interface Descriptions	0
10.1. LCD Interface	0
10.2. CTP Interface	0
11. Backlight Example Circuit	0
12. LCD Timing Details	0
12.1. Timing Chart	0
12.2. Timing Characteristic	0
12.3. SYNC Mode Timing Diagram	0
12.4. SYNC-DE Mode Timing Diagram	0
12.5. Reset Timing	0
12.6. Power On Sequence	0
12.7. Power-off Sequence	0
13. Reliability Test	0
14. Precautions for Using LCD Modules	0
14.1. Handling Precautions	0
14.2. Storage Precautions	0
15. Revision History	0
16. Legal Information	0
16.1. Proprietary Information	0

1. General Specification

4DLCD-43480272-IPS is a colour active matrix LCD module incorporating amorphous silicon TFT IPS (Thin Film Transistor). It is composed of a colour TFT-LCD panel, driver IC, FPC and a backlight unit with/without a Resistive/ Capacitive Touch Panel (RTP or CTP), and with/without Cover Lens Bezel (CLB). The module display area contains 480 x 272 pixels. This product accords with RoHS environmental criteria.

Part Number Details:

4DLCD - 4D Systems LCD Display

43480272 - 4.3-inch, 480 x 272 Resolution

IPS - In-Plane Switching

RTP - Resistive Touch

CTP - Capacitive Touch

CLB - Cover Lens Bezel



Note

- RoHS compliant
- LCD weight tolerance: $\pm 5\%$.